

Series DIBV

DUCTILE IRON THREADED BODY OILFIELD BALL VALVE

- **Size :** 1" FP , 2" RP , 2"FP , 2.5"FP , 3"RP , 3" FP , 4"RP , 4"FP
- **Port:** Full Port / Reduced Port
- **Pressure:** 1000PSI ,1500PSI, 2000PSI NSCWP
- **BODY / CAP:** ASTM A395 60-40-18 Ductile Iron
- **SEAT:** RPTFE / DELRIN
- **BALL / STEM :** SS TRIM SS420 / SS304 / SS316
- **Max Temp.:** 180°F
- **Ends:** ASME B1.20.1(NPT)
- Threaded Body Construction
- Blow-out-Proof Stem
- NACE MR-0175
- Lockable Lever Handle
- Test Standard: API598

DIBV SERIES - AVAILABLE SIZES										
Pressure	Paint Color	1" FP	1.5" FP	2" RP	2" FP	2.5" FP	3" RP	3" FP	4" RP	4" FP
1000 PSI		●		●	●	●	●	●	●	●
1500 PSI		●		●	●	●	●	●	●	●
2000 PSI		●		●	●	●	●	●	●	●

Series CSBV

CARBON STEEL THREADED BODY OILFIELD BALL VALVE

- **Size :** 1" FP , 2" RP , 2"FP , 2.5"FP , 3" FP , 4"RP , 4"FP
- **Port:** Full Port / Reduced Port
- **Pressure:** 2500PSI ,3000PSI ,5000PSI NSCWP
- **BODY / CAP:** ASTM A216 WCB Carbon Steel
- **SEAT:** DELRIN
- **BALL / STEM :** SS TRIM SS420 / SS304 / SS316
- **Max Temp.:** 180°F
- **Ends:** ASME B1.20.1(NPT) / API 5B LP
- Threaded Body Construction
- Blow-out-Proof Stem
- NACE MR-0175
- Lockable Lever Handle
- Test Standard: API598

CSBV SERIES - AVAILABLE SIZES										
Pressure	Paint Color	1" FP	1.5" FP	2" RP	2" FP	2.5" FP	3" RP	3" FP	4" RP	4" FP
2500 PSI		●		●	●	●		●	●	●
3000 PSI		●		●	●	●		●	●	●
5000 PSI		●		●	●	●		●		

Series A2BV

FORGED STEEL THREADED BODY OILFIELD BALL VALVE

- **Size :** 1" FP , 2" RP , 2"FP , 2.5"FP , 3"RP , 3" FP , 4"RP , 4"FP
- **Port:** Full Port / Reduced Port
- **Pressure:** 2500PSI ,3000PSI ,5000PSI NSCWP
- **BODY / CAP:** ASTM A105 Carbon Steel / 4130 Low Alloy Steel
- **SEAT:** DELRIN / PEEK
- **BALL / STEM :** SS TRIM SS420 / SS304 / SS316
- **Max Temp.:** 180°F
- **Ends:** ASME B1.20.1(NPT) / API 5B LP
- Threaded Body Construction
- Blow-out-Proof Stem
- NACE MR-0175
- Lockable Lever Handle
- Test Standard: API598



A2BV SERIES - AVAILABLE SIZES

Pressure	Paint Color	1" FP	1.5" FP	2" RP	2" FP	2.5" FP	2-7/8" FP	3" FP	4" RP	4" FP
2500 PSI		●	●	●	●	●	●	●	●	
3000 PSI		●	●	●	●	●	●	●	●	
5000 PSI		●	●	●	●	●	●	●		

Series ABBV

CARBON STEEL BOLTED BODY OILFIELD BALL VALVE

- **Size :** 1" FP , 2" RP , 2"FP , 2.5"FP , 3"RP , 3" FP , 4"RP , 4"FP
- **Port:** Full Port / Reduced Port
- **Pressure:** 2500PSI ,3000PSI ,5000PSI NSCWP
- **BODY / CAP:** ASTM A105 Carbon Steel / 4130 Low Alloy Steel
- **SEAT:** DELRIN / PEEK
- **BALL / STEM :** SS TRIM SS420 / SS304 / SS316
- **Max Temp.:** 180°F
- **Ends:** ASME B1.20.1(NPT) / API 5B LP
- Bolted Body Construction
- Blow-out-Proof Stem
- NACE MR-0175
- Lockable Lever Handle
- Test Standard: API598



ABBV SERIES - AVAILABLE SIZES

Pressure	Paint Color	1" FP	1.5" FP	2" RP	2" FP	2.5" FP	3" RP	3" FP	4" RP	4" FP
2500 PSI		●	●	●	●		●	●	●	●
3000 PSI		●	●	●	●		●	●	●	●
5000 PSI		●	●	●	●		●	●		●

Series EUECBV

EUE 8RD THREADED BODY OILFIELD BALL VALVE

- **Size :** 2-3/8" FP , 2-7/8" FP
- **Port:** Full Port
- **Pressure:** 2000PSI ,3000PSI, **3600PSI** NSCWP
- **BODY / CAP:** ASTM A216 WCB Carbon Steel
ASTM A351 CF8M Stainless Steel
ASTM A105
- **SEAT:** DELRIN
- **BALL / STEM :** SS TRIM SS420 / SS304 / SS316
- **Max Temp.:** 180°F
- **Ends:** ASME B1.20.1(NPT)
- Threaded Body Construction
- Blow-out-Proof Stem
- NACE MR-0175
- Lockable Lever Handle
- Test Standard: API598

EUECBV SERIES - AVAILABLE SIZES			
Pressure	Paint Color	2-3/8" EUE x 2-1/16" Bore	2-7/8" EUE x 2-9/16" Bore
2000 PSI			
3000 PSI			
3600 PSI			

Series EUECBV

FREEZE RESISTANT BALL VALVE

- **Size :** 2" RP , 3"RP ,4"RP
- **Port:** Reduced Port
- **Pressure:** 750 PSI - 2000 PSI NSCWP
- **BODY / CAP:** ASTM A395 60-40-18 Ductile Iron
- **SEAT:** RPTFE
- **BALL / STEM :** Stainless Steel TRIM
- **Max Temp.:** 380°F
- **Ends:** ASME B1.20.1(NPT)
- Threaded Body Construction
- Blow-out-Proof Stem
- NACE MR-0175
- Lockable Lever Handle
- Test Standard: API598

FRB SERIES - AVAILABLE SIZES				
Pressure	Paint Color	2" RP	3" RP	4" RP
1000 PSI				
1500 PSI				
2000 PSI				